HIGH-DENSITY **MINIATURIZATION HIGH-SPEED DATA TRANSFER** RELIABILITY

- Signal & Power
- Designed and tested to high-speed data transfer protocols
- IP68 watertight, 20 meters, 24 hours





SS← HDMI®











1:1 SIZE COMPARISON

BODY STYLES



BODY STYLES

PLUGS

CABLE MOUNTED

RECEPTACLES

PANEL & CABLE MOUNTED







BODY STYLES

MR50

Cable mounted

Panel rear-mounted

Up to 45% smaller



All dimensions shown are in millimeters and are for reference only.

LOCKING SYSTEMS







Push-pull

Screw-locking

Quick-release

COLORS

MiniMax is available in two housing colors: Nickel ANTHRACITE and Chrome BLACK.

Anthracite

standard





Black optional

ETHERNET 8-PIN 10Gb/s



A unique robust and sealed miniature connector for Ethernet applications in harsh environments.

- AWG24, compatible with long range standard Ethernet cables
- Symmetrical hermaphroditic contact block
- 0.5mm contacts

ACCESSORIES


- Soft caps
- Straight bend relief
- Right-angle heat shrinking tube
- PC-Board termination
- Fischer Rugged Flash Drive for safe mobile data transfer

USB 3.0 9-PIN



Optimized design for full USB 3.0 performance. Tested to the full S-parameter standards with cables up to 2 meters.

- Advanced power contacts
- Hermaphroditic contact block
- 0.5mm contacts



CABLE ASSEMBLY SOLUTIONS

■ Rugged & submersible solutions

■ Cable assembly with straight or angled 60° and 90° overmolding

■ Bend relief





For more information visit fischerconnectors.com/minimax

